EPDM - Commercial Grade - 60A

Specifications
August 2024

Description:	Ethylene Propylene Diene Monomer (EPDM) and SBR blended sheet is a black colored sheet rubber which provides very good resistance to weathering, ozone and UV exposure.
Compound:	10% Ethylene Propylene Diene Monomer (EPDM) Base, SBR
Color:	Black
Weight:	Approximate weight per square foot: 1/8" weighs 1-1/4 lbs.
Durometer:	60 Shore A, +/- 5
Temperature Range:	-40 F to 212 F
Minimum Tensile:	725 PSI or 5 MPA
Finish:	Smooth
Minimum Elongation:	300%
Gauges:	1/32”, 1/16", 3/32”, 1/8", 3/16", 1/4", 3/8", 1/2", 3/4” (custom gauges up to 2” thick are available upon request)
Widths:	36" (custom widths up to 78” are available upon request)
Roll Length:	25’ or 50’ depending on thickness.
PSA:	Pressure sensitive adhesive can be applied to this product upon request.
Chemical Resistance:	Good resistance to UV rays and ozone. Good resistance to Anti-freeze, Synthetic Detergents, Acetone, Boric acid, Ethanol, Formaldehyde, Mercury, Potassium Sulfate, Silver Nitrate, Steam (up to 212 Fahrenheit), Saccharin. For EPDM Blend's compatibility with your specific medium please consult a Rubber-Cal representative.
Applications:	Provides outstanding resistance to weathering, ozone and UV exposure. Gasket, bumper and general exterior applications.
Flexibility:	This medium durometer (55-65) sheet rubber offers good pliability and elasticity.
Custom Cuts:	In addition to hand fabrication, this product can be fabricated using laser, die, and water-jet cut. Please submit your drawings for a price quote.
Availability:	Popular gauges are generally in stock.
California Prop 65:	⚠**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Rubber Cal

Specifications and/or prices are subject to change without prior notice.
© 2021 Rubber-Cal all rights reserved.
Rubber-Cal, Inc.
18424 Mt Langley St,
Fountain Valley, CA 92708
800-370-9152
www.rubbercal.com